

# 2011 BMW F 800 R

**MSRP: \$9,950.00\*** Destination charge (not included in MSRP): \$495



Copyright 2011 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.  
 \*Actual price determined by dealer. Price excludes taxes, license, options and handling charge.  
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	3.50 x 17 cast aluminum
Bore x Stroke	82 mm x 76 mm	Rear Wheel	5.50 x 17 cast aluminum
Displacement	798 cc	Front Tire	120/70 x ZR 17
Horsepower	87 bhp @ 8000 rpm	Rear Tire	180/55 x ZR 17
Torque	63 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	84.4 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	35.6 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	59.8 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.1 quarts	Seat Height	31.5 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	65.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	390 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	439 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	893 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code	Price
<b>Drivetrain</b>		N07	N / C
Primary Drive	1:1.943	N66	N / C
Clutch	Wet multi plate	N67	N / C
1st Gear Ratio	2.46:1	N80	\$650
2nd Gear Ratio	1.75:1	Standard Equipment	
3rd Gear Ratio	1.38:1	588	N / C
4th Gear Ratio	1.23:1	Available Equipment	
5th Gear Ratio	1.13:1	519	\$250
6th Gear Ratio	1.04:1	524	\$900
Final Drive System	Chain	530	\$250
Final Drive Ratio	2.35:1	539	\$295
<b>Frame and Suspension</b>		560	\$250
Frame	Aluminum bridge, engine partly load bearing	603	\$395
Front Suspension	43 mm telescopic fork	764	\$50
Front Travel	4.9 inches	774	N / C
Rear Suspension	Double sided aluminum swingarm	778	N / C
Rear Travel	4.9 inches		
<b>Brakes</b>			
Brake System	Front and rear disc with optional ABS		
Front Brakes	Double floating discs, four-piston fixed caliper		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	single disc, single-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		