

2012 BMW F 800 GS

MSRP: \$12,355.00* Destination charge (not included in MSRP): \$495



Copyright 2012 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	2.15 x 21 spoked wheel with aluminum rim
Bore x Stroke	82 mm x 76 mm	Rear Wheel	4.25 x 17 spoked wheel with aluminum rim
Displacement	798 cc	Front Tire	90/90 x 21
Horsepower	85 bhp @ 7500 rpm	Rear Tire	150/70 x 17
Torque	61 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	91.3 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	37.2 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	62.1 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.1 quarts	Seat Height	34.6 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	408 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	456 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	977 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code	Price
Drivetrain		986	\$N / C
Primary Drive	1:1.943	N93	\$250
Clutch	Wet multi plate	N96	\$0
1st Gear Ratio	2.46:1	Standard Equipment	
2nd Gear Ratio	1.75:1	524	N / C
3rd Gear Ratio	1.38:1	588	N / C
4th Gear Ratio	1.17:1	Available Equipment	
5th Gear Ratio	1.04:1	210	\$450
6th Gear Ratio	0.96:1	519	\$250
Final Drive System	Chain	539	\$295
Final Drive Ratio	2.62:1	603	\$395
Frame and Suspension		636	\$175
Frame	Tubular steel trellis frame	774	N / C
Front Suspension	UPSD fork 45 mm		
Front Travel	9.1 inches		
Rear Suspension	Double sided aluminum swingarm		
Rear Travel	8.5 inches		
Brakes			
Brake System	BMW Motorrad ABS (Switchable) - Standard		
Front Brakes	Dual floating discs, two-piston floating calipers		
Front Rotor	11.8 inch dual floating rotors		
Rear Brake	Single disc, single-piston floating caliper		
Rear Rotor	10.4 inch single rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		