

2013 BMW C 600 Sport

MSRP: \$9,590.* Destination charge (not included in MSRP): \$495



Copyright 2012 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Liquid-cooled in-line twin, 4-stroke	Front Wheel	3.50 x 15 cast aluminum
Bore x Stroke	79 mm x 66 mm	Rear Wheel	4.50 x 15 cast aluminum
Displacement	647 cc	Front Tire	120/70 x ZR 15
Horsepower	60 bhp @ 7500 rpm	Rear Tire	160/60 x ZR 15
Torque	49 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	11.6 :1	Overall Length	84.8 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	34.5 inches
Valves	2 x 31.5 mm intake / 2 x 27.1 mm exhaust	Wheelbase	62.6 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.5 quarts	Seat Height	31.9 inches
Engine Management	BMS-E BMW Digital Engine Management	Steering Angle	64.6 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.6 inches
Fuel Tank	Info. Unavailable	Weight - Dry	509 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	549 lbs. excluding options & accessories
Charging System	588 Watts @ 14 Volts	Maximum Load	981 lbs. GVWR
Battery	12 Volts 12 Amps/hour maintenance-free AGM	Available Colors	
Cooling System	Water-cooling with oil heat exchanger	Code	Price
		764	N / C
			Titan Silver Metallic
		N43	N / C
			Sapphire Black Metallic
		N98	N / C
			Cosmic Blue Metallic Matt
Drivetrain		Available Equipment	
Primary Drive	1.06	198	\$605
Clutch	CVT with centrifugal clutch		Highline Package (heated seats, heated grips, TPM)
1st Gear Ratio	Info. Unavailable	603	\$395
2nd Gear Ratio	Info. Unavailable		Anti-Theft Alarm
3rd Gear Ratio	Info. Unavailable		
4th Gear Ratio	Info. Unavailable		
5th Gear Ratio	Info. Unavailable		
6th Gear Ratio	Info. Unavailable		
Final Drive System	Oil-immersed roller chain		
Final Drive Ratio	1:1.687 (16/27 teeth)		
Frame and Suspension			
Frame	Tubular steel with die-cast aluminum sections		
Front Suspension	Upside-down fork, 40 mm diameter		
Front Travel	4.5 inches		
Rear Suspension	Single-sided swingarm		
Rear Travel	4.5 inches		
Brakes			
Brake System	BMW Motorrad ABS - Standard		
Front Brakes	Dual discs, two-piston floating calipers		
Front Rotor	10.6 inch dual rotors		
Rear Brake	Single disc		
Rear Rotor	10.6 inch single rotor		
Actuation Method	Hydraulic		