

2014 BMW K 1600 GTL

MSRP: \$23,950.00* Destination charge (not included in MSRP): \$495



Copyright 2013 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water/oil cooled in-line 6-cylinder	Front Wheel	3.50 x 17 cast aluminum
Bore x Stroke	72 mm x 68 mm	Rear Wheel	6.0 x 17 cast aluminum
Displacement	1649 cc	Front Tire	120/70 x 17 tubeless
Horsepower	160 bhp @ 7750 rpm	Rear Tire	190/55 x 17 tubeless
Torque	129 lb/ft @ 5250 rpm	Dimensions	
Compression Ratio	12.2 :1	Overall Length	98.0 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	39.4 inches
Valves	2 x 29.0 mm intake / 2 x 24.8 mm exhaust	Wheelbase	66.1 inches
Valves / Cylinder	Four	Ground Clearance	N/A
Engine Oil Capacity	4.8 quarts	Seat Height	29.5 inches
Engine Management	BMW Engine Controller - BMS X	Steering Angle	62.2 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.3 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	708 lbs.
Fuel Capacity	7.0 U.S. gallons including 1 gallon reserve	Weight - Wet	767 lbs.
Charging System	580 Watts @ 14 Volts	Maximum Load	1235 lbs. GVWR
Battery	12 Volts 19 Amps/hour maintenance-free	Available Colors	
Cooling System	Combined water/oil cooling	Code	Price
Drivetrain		N40	N / C
Primary Drive	1:1.617	NB1	N / C
Clutch	Multi-disc, oil bath, hydraulic actuation	NB2	N / C
1st Gear Ratio	2.23:1	Standard Equipment	
2nd Gear Ratio	1.64:1	---	N / C
3rd Gear Ratio	1.32:1	---	N / C
4th Gear Ratio	1.10:1	---	N / C
5th Gear Ratio	0.93:1	---	N / C
6th Gear Ratio	0.79:1	---	N / C
Final Drive System	Enclosed driveshaft	---	N / C
Final Drive Ratio	2.75:1	---	N / C
Frame and Suspension		Available Equipment	
Frame	Bridge-type cast aluminum	134	\$PKG
Front Suspension	BMW Duolever	138	\$450
Front Travel	4.9 inches	182	\$PKG
Rear Suspension	BMW Paralever	416	\$900
Rear Travel	5.3 inches	417	\$400
Brakes		430	\$1000
Brake System	BMW Motorrad Integral ABS - Standard	431	\$1700
Front Brakes	Dual discs, four-piston fixed calipers	530	\$PKG
Front Rotor	12.6 inch dual rotors	603	\$395
Rear Brake	Single disc, two-piston fixed caliper	792	N / C
Rear Rotor	12.6 inch single rotor		
Actuation Method	Hydraulic		