

# 2015 BMW F 800 GS

**MSRP: \$12,190.00\*** Destination charge (not included in MSRP): \$495



Copyright 2014 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.  
 \*Actual price determined by dealer. Price excludes taxes, license, options and handling charge.  
 Prices and specifications subject to change without notice.

| Engine                      |                                                   | Wheels and Tires    |                                          |
|-----------------------------|---------------------------------------------------|---------------------|------------------------------------------|
| Type                        | Water cooled twin cylinder 4 stroke               | Front Wheel         | 2.15 x 21 spoked wheel with aluminum rim |
| Bore x Stroke               | 82 mm x 76 mm                                     | Rear Wheel          | 4.25 x 17 spoked wheel with aluminum rim |
| Displacement                | 798 cc                                            | Front Tire          | 90/90 x 21                               |
| Horsepower                  | 85 bhp @ 7500 rpm                                 | Rear Tire           | 150/70 x 17                              |
| Torque                      | 61 lb/ft @ 5750 rpm                               | Dimensions          |                                          |
| Compression Ratio           | 12.0 :1                                           | Overall Length      | 91.3 inches                              |
| Valve Gear                  | DOHC chain driven with cam followers              | Overall Width       | 37.2 inches                              |
| Valves                      | 2 x 32 mm intake / 2 x 27.5 mm exhaust            | Wheelbase           | 62.1 inches                              |
| Valves / Cylinder           | 4                                                 | Ground Clearance    | Info. Unavailable                        |
| Engine Oil Capacity         | 3.1 quarts                                        | Seat Height         | 34.6 inches                              |
| Engine Management           | BMW Engine Controller - BMS K                     | Steering Angle      | 64.0 degrees                             |
| Fuel Requirement            | Premium Unleaded                                  | Front Wheel Trail   | 4.6 inches                               |
| Fuel Tank                   | HDPE, internal pump and internal filter           | Weight - Dry        | 421 lbs. excluding options & accessories |
| Fuel Capacity               | 4.2 U.S. gallons                                  | Weight - Wet        | 472 lbs. excluding options & accessories |
| Charging System             | 400 Watts @ 14 Volts                              | Maximum Load        | 979 lbs. GVWR                            |
| Battery                     | 12 Volts 14 Amps/hour maintenance-free            | Available Colors    |                                          |
| Cooling System              | 50/50 water/anti-freeze mix, single radiator      | Code                | Price                                    |
| <b>Drivetrain</b>           |                                                   | 751                 | N / C                                    |
| Primary Drive               | 1:1.943                                           | N0D                 | \$250                                    |
| Clutch                      | Wet multi plate                                   | NA5                 | N / C                                    |
| 1st Gear Ratio              | 2.46:1                                            | Available Equipment |                                          |
| 2nd Gear Ratio              | 1.75:1                                            | 218                 | \$PKG                                    |
| 3rd Gear Ratio              | 1.38:1                                            | 235                 | \$675                                    |
| 4th Gear Ratio              | 1.17:1                                            | 416                 | \$350                                    |
| 5th Gear Ratio              | 1.04:1                                            | 431                 | \$505                                    |
| 6th Gear Ratio              | 0.96:1                                            | 499                 | \$250                                    |
| Final Drive System          | Chain                                             | 519                 | \$250                                    |
| Final Drive Ratio           | 2.62:1                                            | 539                 | \$295                                    |
| <b>Frame and Suspension</b> |                                                   | 603                 | \$395                                    |
| Frame                       | Tubular steel trellis frame                       | 633                 | N / C                                    |
| Front Suspension            | Upside-down telescopic fork, 43 mm diameter       | 636                 | \$175                                    |
| Front Travel                | 9.1 inches                                        | 650                 | \$400                                    |
| Rear Suspension             | Double sided aluminum swingarm                    | 681                 | \$150                                    |
| Rear Travel                 | 8.5 inches                                        | 774                 | N / C                                    |
| <b>Brakes</b>               |                                                   | 775                 | \$145                                    |
| Brake System                | BMW Motorrad ABS (Switchable) - Standard          | ZLS                 | \$580                                    |
| Front Brakes                | Dual floating discs, two-piston floating calipers |                     |                                          |
| Front Rotor                 | 11.8 inch dual floating rotors                    |                     |                                          |
| Rear Brake                  | Single disc, single-piston floating caliper       |                     |                                          |
| Rear Rotor                  | 10.4 inch single rotor                            |                     |                                          |
| Actuation Method            | Hydraulic, DOT 4 fluid type                       |                     |                                          |