

2015 BMW F 800 GT

MSRP: \$11,995.00* Destination charge (not included in MSRP): \$495



Copyright 2014 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	3.50 x 17 cast aluminum
Bore x Stroke	82 mm x 76 mm	Rear Wheel	5.50 x 17 cast aluminum
Displacement	798 cc	Front Tire	120/70 x ZR 17
Horsepower	90 bhp @ 8000 rpm	Rear Tire	180/55 x ZR 17
Torque	63 lb/ft @ 5800 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	84.9 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	35.5 inches
Valves	2 x 32 mm mm intake / 2 x 27,5 mm mm exhaust	Wheelbase	59.6 inches
Valves / Cylinder	4-Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.2 quarts	Seat Height	31.5 inches
Engine Management	BMW Engine Controller - BMS K+	Steering Angle	64.2 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.7 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	Info. Unavailable
Fuel Capacity	4.0 U.S. gallons incl. approx. 0.8 gallon reserve	Weight - Wet	470 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	926 lbs. GVWR
Battery	12 Volts 12 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		946 \$100	Dark Graphite Metallic
Primary Drive	1:1.943	NA9 \$100	Montego Blue Metallic
Clutch	Multi-disc, oil bath, mechanical actuation	NB5 N / C	Light White
1st Gear Ratio	2.46:1	Available Equipment	
2nd Gear Ratio	1.75:1	416 \$350	Electronic Suspension Adjustment (ESA)
3rd Gear Ratio	1.38:1	430 \$795	Safety Package (includes 416, 530, 650)
4th Gear Ratio	1.17:1	431 \$505	Comfort Package (includes 519, 539, 636, 681)
5th Gear Ratio	1.04:1	519 \$250	Heated Hand Grips
6th Gear Ratio	0.96:1	530 \$250	Tire Pressure Monitor (TPM)
Final Drive System	Toothed belt drive	539 \$295	On Board Computer
Final Drive Ratio	2.35:1	603 \$395	Anti-Theft Alarm
Frame and Suspension		636 \$175	Center Stand
Frame	Aluminum bridge-type frame w/ load-bearing engine	650 \$400	ASC
Front Suspension	43 mm telescopic fork	681 \$150	Saddle Bag Mounts
Front Travel	4.9 inches	774 N / C	Low Seat
Rear Suspension	Alum. single sided swing arm, central spring strut	775 \$145	Comfort Seat
Rear Travel	4.9 inches		
Brakes			
Brake System	BMW Motorrad ABS - Standard		
Front Brakes	Dual floating discs, four-piston fixed calipers		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single disc, single-piston floating caliper		
Rear Rotor	10.4 inch single rotor		
Actuation Method	Hydraulic		